

# A-1-24 UTL/A-1-30 UTL Specifications



Model	A-1-24 UTL	A-1-30 UTL
Drill Steel Shank	.875" x 3.25" (22.2mm x 82.6mm)	.875" x 3.25" (22.2mm x 82.6mm)
Drill Steel Length U.C.	9"(22.9cm)	12"(30.5cm)
Drill Bit Diameter	.625" – 1.00" (15.9mm to 25.4mm)	.625" – 1.00" (15.9mm to 25.4mm)
*Maximum Drill Depth	7" (17.8cm)	10" (25.4cm)
Drill Distance From Top of Slab	3" - 10" (7.6cm to 25.4cm)	3" - 10" (7.6cm to 25.4cm)
Minimum Cutout Width	24" (61.0cm)	30" (76.2cm)
SCFM Required	32 (0.9 m <sup>3</sup> /min)	32 (0.9 m <sup>3</sup> /min)
PSIG Required	84.5 (5.8 BAR)	84.5 (5.8 BAR)
Weight	75lbs. (34.0kg)	80lbs. (36.3kg)

*Specifications shown are standard. Variations to the standard are available.*

*Dust collection is available.*

*\*Based on 2 piece steel and bits. Whirlybits should be 1" (2.5cm) longer for maximum drilling depth.*