

HydraPaks ~ Gas & Dual-Output

Gas & Dual Output HydraPak Features & Benefits

- ▶ Compact, lightweight hydraulic power source for RGC and other compatible hydraulic tools.
- ▶ Choose from models with Briggs & Stratton and Honda engines.
- ▶ Several models have variable flow and pressure settings.
- ▶ Cart-mounted with large 16 in. pneumatic tires.
- ▶ Low noise level. Much quieter than an air compressor.
- ▶ Easy maintenance and parts replacement.
- ▶ Controls easily accessible for safety and comfort.
- ▶ Electric start and low oil shutdown on all models.
- ▶ Powder-coated tubular steel frame protects unit from damage.
- ▶ Lifting eye and detachable handles for easy transporting and storage.
- ▶ 6 gallon oil reservoir and heavy duty 8-tube heat exchanger are standard on most models.
- ▶ HydraPaks with 18 hp Briggs & Stratton engines are equipped with an electronic governor.



HV1658 Gas HydraPak

- ▶ Dual-output HydraPaks can power two tools simultaneously.
- ▶ Full set of gauges, extra heavy-duty 10-tube heat exchanger and 6 gallon removable gas tank are standard on the HH2010, HV2310 and HV2312.
- ▶ Same as above for the HV351212 except for an extra heavy-duty 12-tube heat exchanger.

Gas HydraPak Specifications

Model	HV1658	HV1858	HH2010	HH2210	HH2212	HV2310	HV2312
Engine	16 hp B&S Vanguard	18 hp B&S Vanguard	20 hp Honda	22 hp Honda	22 hp Honda	23 hp B&S Vanguard	23 hp B&S Vanguard
Fuel Capacity	9 qt. (8.6 ltr.)	9 qt. (8.6 ltr.)	6 gal. (22.7 ltr.)	6 gal. (22.7 ltr.)	6 gal. (22.7 ltr.)	6 gal. (22.7 ltr.)	6 gal. (22.7 ltr.)
Flow	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	0 - 10 gpm (0 - 38 lpm)	0 - 10 gpm (0 - 38 lpm)	0 - 12 gpm (0 - 45 lpm)	0 - 10 gpm (0 - 38 lpm)	0 - 12 gpm (0 - 45 lpm)
Pressure	2250 psi (155 bar)	2250 psi (155 bar)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)	2000 psi (138 bar) 2500 psi (172 bar) 3000 psi (207 bar)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)	2000 psi (138 bar) 2500 psi (172 bar) 3400 psi (231 bar)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)
Hourmeter	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Weight	226 lbs (103 kg)	240 lbs (109 kg)	285 lbs (129 kg)	360 lbs (163 kg)	360 lbs (163 kg)	290 lbs (127 kg)	290 lbs (127 kg)

NEW



HV351212 Dual-Output HydraPak

Dual-Output HydraPak Specifications

Model	HV1855	HV185510	HV351212
Engine	18 hp B&S Vanguard	18 hp B&S Vanguard	35 hp B&S Vanguard
Fuel Capacity	9 qt. (8.6 ltr.)	9 qt. (8.6 ltr.)	6 gal. (22.7 ltr.)
Flow	Run 2 tools @ 5 gpm (20 lpm) or 1 tool @ 10 gpm (38 lpm)	Run 2 tools @ 5 gpm (20 lpm) or 1 tool @ 10 gpm (38 lpm)	Run 2 tools @ 12 gpm (45 lpm)
Pressure	2250 psi (155 bar)	2250 psi (155 bar)	2250 psi (155 bar)
Hourmeter	Yes	Yes	Yes
Weight	251 lbs. (114 kg)	251 lbs. (114 kg)	355 lbs. (161 kg)

NEW

NEW

Celebrating 70 Years of Quality Construction Products.



REIMANN & GEORGER CORPORATION

www.rgcproducts.com • sales@rgcproducts.com

1.800.RGC.TOOL (742.8665)



HydraPaks ~ Bi-Directional & Electric

Bi-Directional & Electric HydraPak Features & Benefits

- ▶ Compact, lightweight hydraulic power source for RGC and other compatible hydraulic tools.
- ▶ Cart-mounted with large 16 in. pneumatic tires.
- ▶ Low noise level. Much quieter than an air compressor.
- ▶ Easy maintenance and parts replacement.
- ▶ Controls are easily accessible for safety and comfort.
- ▶ Electric start and low oil shutdown on all models.
- ▶ Powder-coated tubular steel frame protects unit from damage.
- ▶ Lifting eye and detachable handles for easy transporting and storage.
- ▶ 6 gallon oil reservoir and heavy duty 8-tube heat exchanger on most models. HE1512 has a 10-tube heat exchanger.
- ▶ Full gauge set is standard on the HE1010 and HE1512.
- ▶ Electric HydraPaks are ideal for indoor work.
- ▶ Choose from 10 hp and 15 hp electric models.
- ▶ Contractors' choice for jobs in hospitals, schools, municipal buildings and other public facilities.
- ▶ Bi-Directional HydraPaks are designed for installing anchoring systems and similar jobs.



HV1858 Bi-Directional HydraPak



Motor Starter



HE1010 Electric HydraPak

Bi-Directional HydraPak Specifications

Model	HH1358C	HV1658C	HV1858C
Engine	13 hp Honda	16 hp B&S Vanguard	18 hp B&S Vanguard
Fuel Capacity	7 qt. (6.5 ltr)	9 qt. (8.6 ltr)	9 qt. (8.6 ltr)
Flow	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)
Pressure	2250 psi (155 bar)	2250 psi (155 bar)	2250 psi (155 bar)
Hourmeter	Yes	Yes	Yes
Weight	228 lbs (103 kg)	228 lbs (103 kg)	249 lbs (113 kg)

Electric HydraPak Specifications

Model	HE1058	HE1058	HE1010	HE1010	HE1512	HE1512
Motor	10 hp Electric	10 hp Electric	10 hp Electric	10 hp Electric	15 hp Electric	15 hp Electric
Electrical Requirements†	208 - 220V, 3 Ph, 60 Hz	460V, 3 Ph, 60 Hz	208 - 220V, 3 Ph, 60 Hz	460V, 3 Ph, 60 Hz	208 - 220V, 3 Ph, 60 Hz	460V, 3 Ph, 60 Hz
Flow	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	0 - 10 gpm (0 - 38 lpm)	0 - 10 gpm (0 - 38 lpm)	0 - 12 gpm (0 - 45 lpm)	0 - 12 gpm (0 - 45 lpm)
Pressure	2250 psi (155 bar)	2250 psi (155 bar)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)	1750 psi (120 bar) * 2000 psi (138 bar) * 2500 psi (172 bar) †	1750 psi (120 bar) * 2000 psi (138 bar) * 2500 psi (172 bar) †
Hourmeter	Yes	Yes	Yes	Yes	Yes	Yes
Weight	221 lbs (100 kg)	250 lbs (100 kg)	250 lbs (118 kg)	290 lbs (132 kg)	290 lbs (127 kg)	310 lbs (141 kg)

* Continuous Duty Cycle † Intermittent Duty Only

Celebrating 70 Years of Quality Construction Products.



REIMANN & GEORGER CORPORATION

www.rgcproducts.com • sales@rgcproducts.com

1.800.RGC.TOOL (742.8665)

