

## Portable Diaphragm Pumping Systems



5HP & 9 HP

DPS9

Marathon offers two types of portable spraying systems to suit your material requirements. The DPS5 is effective for the application of cold-pour crack fillers and the DPS9 offers the added versatility for spraying coal tar with sand, latexes, primers, plus cold pour crack fillers. Both units provide greater efficiency because the system automatically shifts to neutral when the spray wand is shut off.

### Features

- 6 ft. suction hose with 40" steel pipe.
- Surge tank stops pulsation to allow even spray pattern.

### Options

- 210 gallon non-agitated tank for cold pour crack filler applications.



4390 Corporate Drive  
Burlington, Ontario CANADA L7L 5R3  
Tel: (905) 335-0000  
Fax: (905) 335-9990  
[www.MarathonEquipmentInc.com](http://www.MarathonEquipmentInc.com)

<b>Models</b>	<b>DPS5</b> (Coal tar with sand, cold-pour crack filler)	<b>DPS9</b> (Coal tar with sand, primer, latex, cold-pour crack filler)
<b>Shipping Weight</b>	225 lb (102 kg)	280 lb (127 kg)
<b>Dimensions</b>		
Overall Length	66" (167 cm)	64" (162 cm)
Overall Width	23" (58 cm)	24" (61 cm)
Overall Height	29" (73 cm)	29" (73 cm)
<b>Material Pump</b>	1" discharge, air-operated dual diaphragm.	1" discharge, air-operated dual diaphragm.
<b>Air Compressor Pump</b>	8.1 scfm, 100 psi	15.5 scfm, 100psi (max. 150psi)
<b>Air Compressor Engine</b>	5.5hp Honda	9hp Honda
<b>Spray Hose &amp; Wand</b>	Spray wand with shut-off valve and spray tip comes with ½" X 30ft. spray hose.	Spray wand with shut-off valve and spray tip comes with ½" X 75ft. spray hose.
<b>Basket Strainer Filtration System</b>	Standard	Standard
<b>Surge Tank</b>	Standard	Standard

*Specifications subject to change without notice*