

SELICK

STM Series



Powered by Tier 4 Compliant Diesel Engine



**Truck Mounted Forklift
Three Wheel Drive
5,500 - 7,000 lb capacity**

- ***Powerful***
- ***Clean***
- ***Versatile***

Truck Mounted Forklifts



Model Name	Lift Capacity
STM55	5,500 lbs at 24" load centre
STM55P	Pantograph mast with 5,500 lbs at 24" load centre
STM70	7,000 lbs at 24" load centre

Standard specifications

- Side mount operator platform for optimum visibility to load.
- Powerful Tier 4, direct injection, electronic diesel engine uses the latest exhaust technology to meet the strict EPA standards required for Tier 4 compliance.
- Customizable options available to meet the needs of specific applications in any industry.

Engine



Kohler KDI 1903TCR Tier 4 final 3 cylinder engine does not require exhaust aftertreatment. Diesel Particulate Filter (DPF) and Diesel Exhaust Fluid (DEF) are **not** required reducing operating costs.

- 56 hp at 2,600 rpm
- Dual element air filter
- Water separator
- Cold weather starting aid.
- Torque rating 166 ft-lbs @ 1,500 rpm.

Transmission

- Hydrostatic transmission
- Full-time 3-wheel drive
- Inching control for precise load placement.
- "EZ Trac" traction control provides hands-free disengagement when improved surfaces are sensed reducing heat and wear on components.

Hydraulics

- 5-spool hydraulic valve with easy-to-reach controls
- Stabilizers

Steering

- Priority load sense steering

Operator compartment

- Roomy, side-mounted operator's compartment meets/exceeds ANSI B56.6 ROPS/FOPS standard.
- Adjustable driver's seat with retractable seatbelt
- Automotive style controls
- Operators manual with latched storage compartment
- Safety decal package.

Instrumentation

- Instrumentation: Fuel level, hour meter, battery, oil pressure warning, engine temperature, preheat, trac-loc, headlight, parking brake, air filter restriction.
- Horn, backup alarm and traction control switch
- Neutral safety start.

Tires

- Standard 31" all-terrain tires for all job sites.
- Optional sizes/tread patterns for any application.

Mast assemblies

- Lift heights to 8, 10, 12 feet. Sellick SEE-THRU® design.
- Corrosion resistant chain.

Carriages

- 48" ITA hook Class IIIB

Electrical

- Voltage: 12 V; alternator: 80A; battery: 875 CCA.
- Sealed ECU and fuse box.
- LED brake and reverse lights for transporting.

Mounts

- Universal easy-to-install mounts fit most truck/trailers.

Standard features


- Retractable seatbelt
- Electrical light cord
- Parts CD
- Halogen lighting includes 2 front & 1 rear worklight
- Safety lighting includes LED brake/amber warning lights
- Backup alarm
- Spring applied, hydraulic release park brake
- Neutral safety start

Optional Equipment

- Tilt steering column
- Fork positioner
- Strobe light
- Cold weather package
- Custom paint



Truck Mounted Forklifts



Model	Ref	STM55	STM55P	STM70
Lift capacities @ 24" load centre		5,500 lbs/2,500 kg	5,500 lbs/2,500 kg	7,000 lbs/3,175 kg
Base operating weight		6,450 lbs/2,926 kg	7,650 lbs/3,470 kg	7,050 lbs/3,198 kg
Overall length (without forks)	A	102"/2,591 mm	105.5"/2,680 mm	
Overhang		63"/1,600 mm	73"/1,854 mm	67"/1,702 mm
Overall width	B	100"/2,540 mm		
Height to top of OHG	C	96"/2,438 mm		
Frame opening	D	60"		
Outside turning radius		120"/3,048 mm	123"/3,124 mm	
Mast sideshift		6"/152 mm		6"/152 mm
Mast underclearance	E	12"/305 mm		12"/305 mm
Mast tilt - forward	F	12°		
Mast tilt - rearward	G	10°	8°	10°
Gradeability		25%		
Wheelbase	H	66"/1,676 mm	74"/1,880 mm	74"/1,880 mm
Tire Size		31 - 15.5 - 15		31 - 15.5 - 15
Engine build/model		Kohler KDI 1903TCR Tier 4 compliant		
Engine type		Diesel, turbocharged, electronic		
Cylinders		3		
Engine output		56 hp		
Transmission type		Hydrostatic		

Because of our constant dedication to product improvement, all specifications are subject to change without notice.

— All Sellick forklifts meet or exceed all ANSI B56.6 safety standards. —



Cold Climate Package



Heated Cab



Custom Paint



Pantograph Reach

sellick

Working for you

Built in the Sellick tradition of quality & reliability, the STM Series is supported by a network of long-established material handling dealers that provide prompt parts and service. All Sellick products are backed by one of the best warranties in the business.

All Sellick forklifts meet or exceed all ANSI B56.6 safety standards.



Sellick Equipment Limited

P.O. Box 1000/358 Erie Street North
Harrow, Ontario, Canada N0R 1G0
519-738-2255 • sellick@mnsi.net
Visit us at www.sellickequipment.com



Sold & serviced by: