

Ride-On Power Asphalt Sprayers

240 Gallon Capacity

PAS240R-R

These units have been designed for the quick and efficient application of rejuvenating sealers and asphalt cutbacks. The material tank will hold up to 240 gallons and the rear spray bar is easily activated by a finger-tip controlled toggle switch mounted on the drivers console to maximize productivity and material control.



Features & Benefits

- This rugged ride-on spray unit is built on an industrial grade chassis and is designed to provide years of trouble free service.
- 10" diameter lid assembly provides quick and easy filling of material tank.
- Easy to adjust pressure relief valve offers quick adjustment of spraying pressure to optimize material performance.
- Conveniently located, adjustable spray bar provides even distribution of material while minimizing over spray.
- Each nozzle is equipped with a shutoff valve to fine tune the application of sealer to specific conditions.
- Clogged pumping systems and nozzles are virtually eliminated with a standard basket strainer.
- Dual rear view mirrors provide a safe view of the rear of the vehicle.
- Air pressure for shutoff valve control is provided by a self contained air compressor complete with pressure regulator and reservoir tank.
- The spray bar is activated by a remote control on the vehicle's dashboard.
- Dash mounted gauges monitor fuel level, voltage, hours run and control system air pressure.
- The pumping system is powered by a reliable 11hp Honda engine, driving a 25 gpm pump.
- A tank lift system provides easy, safe access to the engine compartment for routine maintenance of the vehicle.
- Maximum vehicle speed is 22mph.
- Increased corrosion resistance with epoxy primer and standard blue paint finish.

NOTE: This unit is not a motor vehicle as defined in the National Traffic Vehicle Safety Act and is not implied for licensing as a motor vehicle or for usage on roads, streets and/or highways.

Options

- 24" wheeled curb edger with 2 spray tips.
- Strobe light.
- Customers choice of paint colour.



4390 Corporate Drive
Burlington, Ontario CANADA L7L 5R3
Tel: (905) 335-0000
Fax: (905) 335-9990
www.MarathonEquipmentInc.com

PAS240R-R



Models	PAS240R-R (for rejuvenating sealers)	PAS240R-C (for asphalt cutback, Gilsonite, etc.)	RIDE-ON VEHICLE:	
Shipping Weight	2334 lb (1061 kg)	2334 lb (1061 kg)	Engine	22hp Kohler.
Dimensions	Unit Without Spray Bar	Unit Without Spray Bar	Drive System	6 speed transmission (hi-lo range).
Height:	53" (1346 mm)	53" (1346 mm)	Suspension	Heavy duty multi-leaf rear suspension and Dual coil springs, dual shocks on front suspension.
Width:	58" (1473 mm)	58" (1473 mm)		
Length:	128" (3251 mm)	128" (3251 mm)		
Length:	Spray Bar (varies) 88" (2235 mm) and up	Spray Bar (varies) 80" (2032mm) and up	Fuel Capacity	7 gallons (26 Liters).
TANK AND SPRAYING SYSTEM:			Brakes	4 wheel hydraulic drum brakes.
Capacities			Electrical	12 volt battery, 25 amp. alternator, electric start with clutch safety switch, twin halogen headlights.
Loading Height	53" (1346 mm)	53" (1346 mm)	Body	Plastic cowl, fenders and hood.
Material Tank	240 gal. (1089L)	240 gal. (1089L)	Steering	Front wheel power steering; automotive type 14" steering wheel with tilt mechanism.
Flushing Tank	6 gal. (23L)	N/A	Main Frame	Welded steel frame construction, mid engine placement.
Engine	11hp Honda	11hp Honda	Drive Controls	Foot operated accelerator, clutch and brake Pedals; shift lever with H-shift pattern.
Pump	25GPM	25GPM		
Spray Wand Assembly	N/A	4ft. hand held wand with spray gun and shut-off valve, 100ft. hose and hose reel.		
Spray Bar Assembly	Air operated.	Air operated.		
Asphalt Rate Meter	Standard	Optional		
Hose Reel	Optional	Standard		

Specifications subject to change without notice.

Power Asphalt Sprayers

Marathon's 200 gallon skid or trailer mounted Sealer Sprayers were developed with affordability in mind. These non-heated units are designed for use with driveway sealer material such as Gilsonite, asphalt cutback, solvent based sealers, foundation coatings and concrete primers.



PAS200T

Features & Benefits

- Long lasting all welded construction – not bolted.
- Thick sheet metal panels exceed the standard used in competitive products.
- 100 ft. sealer hose complete with spray wand.
- 4" diameter filler hole.
- 1" drain.
- Increased corrosion resistance with epoxy primer and standard blue paint finish.



PAS200S



PPAS10

Options

- Skid mounted – no chassis.
- 130 gallon capacity also available.
- 9hp Honda engine with 18 gpm pumping system.
- Additional spray wand with 100 ft. hose.
- Hose reel with stainless steel swivel.
- 10" diameter filler lid.
- Heated tank available.
- 1" material transfer valve.
- Customer's choice of paint colour.

Specifications subject to change without notice.



4390 Corporate Drive
 Burlington, Ontario CANADA L7L 5R3
 Tel: (905) 335-0000
 Fax: (905) 335-9990
www.MarathonEquipmentInc.com

Models	PAS115S	PAS200S	PAS200T	PPAS10
Shipping Weight	376 lb (171 kg)	450 lb (204 kg)	1100 lb (500 kg)	55 lb (25 kg)
Type	Skid mounted	Skid mounted	Trailer mounted	Portable
Dimensions				
Overall Length	40" (102 cm)	48" (121 cm)	120" (305 cm)	23" (58 cm)
Overall Width	40" (102 cm)	42" (106 cm)	67" (170 cm)	21" (53 cm)
Overall Height	17" (43 cm)	46" (116 cm)	67" (170 cm)	17" (43 cm)
Loaded Height	N/A	38" (96 cm)	47" (119 cm)	N/A
Capacity	115 gal (434 L)	210 gal (793 L)	210 gal (793 L)	N/A
Air Cooled Engine	5.5hp Honda	5.5hp Honda	5.5hp Honda	5.5hp Honda
Pump Capacity	10 gpm	10 gpm	10 gpm	10 gpm
Axle Capacity	N/A	N/A	Single 3500 lb (1591 kg)	N/A
Tire - size			(2) 225/75R15 Tires	