

T7500 Truck Mounted 3 Easy Steps to Smoother Roads



Apply Tack Coat




**Inject Emulsion
Aggregate Mixture**



**Cover With Dry
Aggregate**

The Free
Travel
Boom
System
Has a
Working
Radius of
18 Feet.



**Free Travel
Boom System**

**74 Hp It4 Diesel
Engine** (Fully
Enclosed)

**Air Conveyor Aggregate
Feed System** (Venturi feed
no moving parts)



**L.E.D. Directional
Light Stick**

Emulsion Tank

AMSE Certified 250
Gallon with 12" lid.

**120v Overnight
Heating System**

Costly, inefficient road repair has long been a thorn in the side of many people - from city and county officials to the taxpayers who use the road. The Total Patcher T7500 is the solution to their problem. **Use the Total Patcher T7500 Road Repair System, and everybody wins!**

In only three simple steps, the **Total Patcher T7500** allows the repair crew to quickly and efficiently create a **permanent repair** without having to close the road. Traffic stays moving and road repair costs are minimized. No more repetitive trips to fix the same area!

Economical

- Material cost is about 1/2 **the cost** of cold mix
- Repairs last for years
- Store materials on-site for **increased efficiency**
- **No other equipment necessary**= aggregate is supplied by your dump truck. The Vortex does the rest!
- Produce **20 tons (or more)** of road repair patch **daily**

T7500 Will Repair

- Potholes
- Alligator Cracks
- Shoulder Failures
- Utility Cuts
- Cracks (using crack seal attachment)
- Many other common road repairs

Total Patcher T-7500 Truck Mounted Features:

Container Capacity

- **Size** - Available in 3 to 10 cubic yard capacity; Custom sizes also available, contact us for details.

Emulsion Tank

- **Size** - 250 U.S. gal; 12-inch filler cap for added safety and convenience
- **Working Pressure** - 200 psi @ 500° F pressure relief set from 100-110 psi
- **Insulation** - R-15 rating with a fire retardant fiber reinforced plastic cover
- **Heat** - Two 1500w radiant heater blankets (120v) with thermostatic control

Emulsion Line Clean Out Tank

15 U.S. gal pressure vessel rated at 200 psi @ 450° F pressure relief set at 175 psi

Engine Fuel Tank

18.5 U.S. gal steel with quantity gauge

Compressor

Auxiliary driven 15 cfm continuous duty; governor set @ 125 psi (Emulsion tank regulated @ 90 psi)

Blower

450 cfm with 7 psi (14 psi potential) @ 1500 rpm, approx 42 BHP. Mounted directly off engine flywheel (requires no belts or pulleys). Protective air pop-off valve set at 10 psi. Normal operating temp under 230° F (max 275° F).

Air Conveyor Aggregate Feed

Hopper box on patcher receives aggregate via a 5" dia flex hose from dump truck. Aggregate is injected into the air conveyor system via a low pressure suction created by a venturi (under the hopper box). Slide gate opens and closes by a 4" stroke air ram controlled through a 12v air solenoid valve activated by a remote switch located at operator control handle. Aggregate 1/4" - 1/2" size is normally used. Machine will run up to 1" aggregate, and will allow a 2 1/2" stone to pass through without clogging. Air solenoid valve has manual override for easy servicing.

Air Filters

- **Engine** - Paper element with vactuator valve in filter housing
- **Compressor** - Paper element with vactuator valve in filter housing
- **Blower** - Paper element with 300 sq inches in filtration surface with foam pre-cleaner

Mobile Heating System

Engine coolant is routed through a high efficiency heat exchanger filled with heat exchange oil. The heated oil circulates via a 12v circulation pump throughout the emulsion distribution system, including the emulsion storage tank, hoses, and spray nozzle. Average system temp is 140° F. The total patcher can work effectively down to an ambient temp of 0° F (using proper emulsion for those temperatures).

Vented Nozzle/Spray Tip

Nozzle - Lightweight steel tube 3 1/2" x 13" automatically pressure compensates to prevent blowing material out of target area. Promotes clean operation and precise control.

Spray tip - Singular heated block with a precession laser cut 1" x .0625" inch slot for dispensing emulsion for 100% aggregate coating.

Aggregate Hose

Aggregate travels the length of the machine via a 3 1/2" ID schedule 40 pipe, then travels through 3 1/2" ID 192" long rubber neoprene lined hose (wire reinforced to prevent kinks).

Emulsion Supply/Diesel Clean-Up Line

A 20' long x 1/2" ID hose rated at 2300 psi carries the emulsion to the spray nozzle. Emulsion lines are encased in an insulated line packet to allow for cold weather operation. This line also serves as the clean-up line when patching operations are completed. Clean up takes about 1 quart of liquid.

Swinging Hose Carrier

Easy Operation - Free travel boom system supports the weight of the aggregate hoses. System allows an 18" working travel radius. All operator controls for throttle and aggregate flow are at the handle.

GENERAL TRUCK SPECIFICATIONS

- **Chassis:** Conventional or tilt cab
- **GWV:** 18,000 kg or 39,600 Lb
- **Load Capacity:** Min. 24,000 Lb
- **Lights** - Brake & tail, side marker, multi-directional/multi-pattern high intensity LED light stick, rear mounted strobe

Specifications subject to change without notice

Total Patcher

4614 East 1000 North-Pittsboro, Indiana 46167

Toll Free 866-892-4737-Ph: 317-892-4737- Fax: 317-892-5196

Info@totalpatcher.com - www.totalpatcher.com